ascension WHEELCHAIR LIFTS

Every facility is different. Ascension offers the ability to fit your lift to your specific needs.

Standard	●
Optional	O
Not Available	-
External to Lift, Optional	❖

Lift Options	Clarity	Virtuoso		Protégé	
	Permanent	Portable	Permanent	Portable	Permanent
Automatic Gate Operator(s), Upper and/or Lower	O	O	O	O	O
Communication - Two Way	O	O	O	O	O
Compression Feature	-	●	●	●	●
Drive System - Chain Hydraulic	●	-	-	-	-
Drive System - Direct Hydraulic	-	●	●	●	●
Electrical – Internal Battery Backup	●	❖	❖	❖	❖
Electrical Configured for 230VAC	O	O	O	O	O
Enclosure – Dome & Ventilation	O	-	-	-	-
Enclosure – Full Aluminum/Plexiglas Runway	●	-	-	-	-
Enclosure – Installed in Shaft/Runway By Others	O	-	-	-	O
Entry/Exit - Same Side	O	-	-	-	-
Entry/Exit - Straight Through	●	●	●	●	●
Key Switches – Universal	O	O	O	O	O
Lighting - 3-Mode Accent Lighting in Grab Bar	●	-	-	-	-
Lighting - Emergency	●	O	O	O	O
Outdoor Use Package	O	O	O	O	O
Powder Coating - Black Texture	O	●	●	●	●
Powder Coating - Custom Color	O	O	O	O	O
Powder Coating - Silver Metallic	●	O	O	O	O
Safety Pan - Under Platform	-	O	O	●	●
Safety Skirt	-	●	●	-	-

Physical Dimensions			
Platform Size	36" x 56"	36" x 54"	
Lift Size	48 " x 68"	48" x 63"	48" x 58"
Required Space	48" x 68"	52" x 64"	52" x 61"
Vertical Speed (ft per min)	20	7	5
Vertical Travel Range	34" - 168"	12" - 60"	4" - 42"

Standard in all lifts:

Unobstructed View on Three Sides + Upper Landing Gate Window, No Machine Room Needed, Ultra-Slim Platform Floor, Vibration-Isolated Power Unit Supports, Grab Bar, Self-Closing Platform Gates, Electro-Mechanical Door and Gate Interlocks, Lighted Emergency Stop Button with Alarm, Slip-Resistant Platform Floor, Power Requirement: 120V, 13A Max.